

ProTowWash® – Transport Trailer with 370 Gallon Tank

The T400 tandem axle trailer, with your choice of pressure washer, is a fully integrated self-contained pressure washing system. The two 185 Gallon water tanks with integrated baffling provide 370 Gallons of ample water to sustain many remote-cleaning requirements. The dual water tanks provide flexibility for operation and can be either plumbed together or maintained separate. The super duty torsion axle suspension provides the smoothest ride available and prevents damage to equipment from a harsh ride. The enhanced wheel travel (up to 300% over conventional trailers) keeps road vibration and rattle to a minimum.

| TECHNICAL DATA | T400EE | T400S |
|----------------------|--|-------------------------|
| MACHINE CAPACITY | SS, SC, SCU Series (up to 1100# Total) | |
| SUSPENSION / AXLE | Two 3700# Torsion Axles-Up to 300% more wheel travel over conventional trailer | |
| TRAILER BRAKES | Electric brakes rear axle, breakaway switch* | Surge Brake – Rear Axle |
| WHEEL / TIRE | 4 - 14" White Spoke Rims, 5 Lug, ST205/75d 14 Tires, 1760 Pounds capacity per tire | |
| COUPLER / TONGUE | 2" Ball Coupler, Dual 5/16" Safety Chains | |
| VEHICLE HITCH / GVWR | 2" Ball Hitch, Class III 5000 Pound Rated, 21" to top of ball when trailer is attached 5000# GVWR | |
| FENDERS | 12 GA Steel Fender with recessed tail light mount | |
| LIGHTS | Recessed Rubber Grommet Snap-In, 4 Pole Flat Wiring Connector, DOT Approved | |
| JACK | Bolt-On Swing Up Jack 1500# Capacity With Large Swivel Caster 8" Diameter | |
| WATER TANK | 370 gal. total capacity (dual 185 gal) seamless polyethylene, 10" lid, garden hose fill fitting | |
| TANK DRAW / FILTER | 1½" 80 Mesh Strainer with Drain, 1½" Fast Drain Valve | |
| CHASSIS CONST. | 12 GA Steel Frame with Structural Tube Spine, Powder Coat Wrinkle Finish | |
| WEIGHT/DIMENSIONS | 985# Empty (No Machine) 156" Long x 70" Wide x 61" High | |

Note: Specifications subject to change without notification and may vary due to ambient conditions.

Note: Shipped to distributors only – Not available to drop ship – Assembly Required

* Trailers with electric brakes must include a battery power source. We recommend installing a pressure washer equipped with a battery.

Featuring:

- ✓ **Rugged Fender:** Can be used as a step for tank access, will not bend, supports tank.
- ✓ **Recessed Tail Lights:** Will not break off, rubber isolates to reduce bulb failure.
- ✓ **Storage Areas:** Integrated storage tube for spray wands and large (47"x22"x10") storage box at the back of trailer for hoses and other accessories.
- ✓ **Stainless Exhaust Pipe Extension:** Lifetime corrosion resistance insures no need to replace in a few years.
- ✓ **Inlet Plumbing:** System Engineered to prevent pump damage caused by cavitations & contamination

Options...

Hose Reels, Lunette eye hitch, Chrome wheel upgrade, Front Bucket Rack (ACR02), 3-way ball valve (AW006), Pump seal saver bypass (APS50)-installed, Low water shutdown (AW410)-installed, Sand hopper, Light Bar rack (HLB98), Vacuum hose hooks (HHP28), Hydro Vacuum wastewater recycle, 12v chemical sprayer with 40gal tank (AC440), Locking storage lid option (ATH50)



Pressure washer not included
Shown with optional Hose Reel, Light Bar, and front bucket rack



450 641-6633 • 1 866 641-6633
www.multipressionlc.com

WARNING: Trailer brakes and a breakaway switch are recommended and required on the road in most states if the trailer weight exceeds 1500 pounds gross. Check your states requirements.